

How to Order Compressed Gas Pigtails

CREATE A PART NUMBER USING THE CODES BELOW.

	1	2	3	4	5	6	7	8	9	10	11
	HOSE SIZE (1/16")	HOSE STYLE	FITTING OPTION 1ST END	ELBOW OPTION 1ST END	FITTING OPTION 2ND END	ELBOW OPTION 2ND END	FITTING MATERIAL - BOTH ENDS	ARMOR AND/OR TETHER	OXYGEN CLEAN	CGA SPEC. FILL IN WHEN ORDERING	LENGTH * (INCHES)
EX:	4	TD	06		74DV	L	B	A	O	540	36
	4	TS	02	L	02	L	B - Brass	A-Armor	O	320	
		TD	03		03		S6 - 316 SS	T-Tether		326	
		TH	06		06		M - Monel	P-Valve Loop		346	
		TX	06X		06X		C - Carbon			350	
		TZ	07		07		Steel			510	
		TZD	08		08					540	
		3130	31		31					580	
		3160	31FN		31FN					660	
		3R80	32		32					679	
		MDS6	32FN		32FN						
		MDHP	33		33						
		MDM	34		34						
		MDMS	35		35						
			71		71						
			74		74						
			DV		DV						
			71DV		71DV						
			74DV		74DV						

Follow These Simple Steps

Choose the code from each column that defines the part you want to order. Write the codes left to right, in column order, to create a part number.

For Example:

- 1 Select hose size in 16ths of an inch = 4
- 2 Select hose style = TD
- 3 Select the fitting style for the first end = 06
- 4 Select an elbow option for the first end = None
- 5 Select the fitting style for the second end = 74DV
- 6 Select an elbow option for the first end = L
- 7 Select fitting material for both ends = B
- 8 Select A for armor or leave blank for no armor = A
- 9 Select O for oxygen clean or leave blank for no armor = O
- 10 Select CGA style = 540
- 11 Select length in inches = 36"

Part Number - 4TD0674DVLBAO540-36"

1/4" I.D. PTFE inner core, double SS braid, brass female NPT on one end, brass DVP with elbow and CGA 540 hand tight fitting on the opposite end, armor casing, clean for oxygen, 36" length.

*Note about hose lengths:

- A) minimum length of hose without armor = 6"
- B) minimum length of hose with armor = 18"
- C) minimum length of hose with Oxy-Flex style DV on one end = 24"
- D) minimum length of hose with Oxy-Flex style DV on both ends = 24"
- E) over all length is measured to the end of the permanently attached end fitting, not including elbows and/or CGA fittings